

# Mobil Delvac 1130, 1140, 1150

## Heavy-Duty Diesel Engine Oils

### Product Description

Mobil Delvac 1130, 1140, and 1150 are heavy-duty, monograde diesel engine oils formulated with an optimised combination of base oils and a balanced additive system.

### Features & Benefits

Features	Advantages and Potential Benefits
Good protection against rust and corrosion	Longer equipment life and reduced operating costs
Thermal and oxidation stability	Controls sludge build-up and deposits

### Applications

- Diesel and gasoline powered equipment where API CC/SD level performance is required
- On-highway light and medium duty trucking
- Off-highway industries including: construction, quarrying, and agriculture

### Specifications & Approvals

Mobil Delvac 1100 Monogrades are recommended for use in applications requiring:	Mobil Delvac 1130	Mobil Delvac 1140	Mobil Delvac 1150
API CC/SD	X	X	X



## Typical Properties

<b>Mobil Delvac 1100 Monogrades</b>			
SAE Grade	30	40	50
Viscosity, ASTM D 445			
cSt @ 40°C	96	146	226
cSt @ 100°C	11.1	14.5	19.5
Viscosity Index, ASTM D 2270	101	98	98
Sulfated Ash, wt%, ASTM D 874	0.5	0.5	0.5
Total Base #, mg KOH/g, ASTM D 2896	4.1	4.1	4.1
Pour Point, °C, ASTM D 97	-24	-27	-27
Flash Point, °C, ASTM D 92	258	272	269
Density @ 15°C kg/l, ASTM D 4052	0.883	0.888	0.895

## Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

