



Mobil Special 4T 20W40 and 20W-50

Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Special 4T is a general performance four-stroke motorcycle engine oil intended for lubrication of small four-stroke engines.

Features & Benefits

Mobil Special 4T combines highly refined mineral oils and a balanced additive system to prevent build up of deposits and provide wear and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Effective wear protection	Extended engine life
Thermal and oxidation stability, deposit control	Maintains clean engines for smoother operation
Good corrosion protection	Protects critical engine parts and wear surfaces

Applications

Mobil Special 4T is specifically recommended for use in small four-stroke engines; such as those found in smaller motorcycles, lawn mowers, small generators and pumps and in all applications where an API SF and JASO MA level performance is recommended.

Specifications & Approvals

Mobil Special 4T meets or exceeds the following industry specifications:	20W-40	20W-50
API	SF	SF
JASO	MA	MA

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Typical Properties

Filling	RN 4702 BBD	RN 4702 BE
Mobil Special 4T		
SAE Grade	20W-40	20W-50
Viscosity, ASTM D 445		
cSt @ 40°C	A	A
cSt @ 100°C	15.0	A
Viscosity Index, ASTM D 2270	A	A
Sulfated Ash, wt%, ASTM D 874	0.8	A
Pour Point, °C, ASTM D 97	A	A
Flash Point, °C, ASTM D 92	A	A
Density @ 15°C kg/l, ASTM D 4052	A	A

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Special 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

